



AGRI MAXTERIS
Radial Harvesting Tyres



Simply Beyond Harvesting

AGRI MAX TERIS

Radial Harvesting Tyres

- Agri Max Teris have been designed for the most modern harvesting equipments, where flotation and reduced soil compaction is extremely important.
- The casing design, coupled with the large footprint area, guarantee heavy load carrying capacity at low pressure.
- The new designed sidewall protector prevents tyre from damages and in combination with the strong casing with multiple layers of Polyester belts provide an exceptional stability, handling and riding comfort.



AGRIMAX TERIS

Size Range

Size	Load Index	± 2 %		Static Loaded Radius (mm)	Rolling circumference (mm)	RIM		SRI (mm)	Max load capacity		Max Inflation Pressure (bar)
		Section Width (mm)	Overall Diameter (mm)			REC	ALT		At 40 km/h (kg)	At 50 km/h (kg)	
		750/65 R 26	166 A8 / B			764	1636		713	4908	
650/75 R 32	172 A8 / B	655	1789	807	5421	DW21B	DW20B DW23B	825	6300	6300	3.2
800/65 R 32	178 A8 / 175 B	818	1853	833	5615	DW27B	DW25B DH27B	875	7500	6900	3.2
900/60 R 32	181 A8 / 178 B	886	1893	849	5736	DW27B	DW28B DW30B	925	8250	7500	3.2
1050/50 R 32	184 A8 / 181 B	1059	1893	840	5700	36.0VA		875	9000	8250	3.2

Soon Available

- 710/75 R 32
- 620/75 R 26
- 620/75 R 30

Corporate Office:

BKT House
Balkrishna Industries Ltd., C / 15, Trade World, Kamala Mills Compound,
Senapati Bapat Marg, Lower Parel, Mumbai- 400 013, India.
Tel: +91 22 6666 3800 Fax: +91 22 6666 3898

BKT EUROPE SRL

Viale Della Repubblica, 133, 20831 Seregno (MB) - Italy
Tel: +39 0362 33 03 28, +39 0362 32 51 07 Fax: +39 0362 23 24 72

BKT (USA) INC.

2650 West Market St, Akron, OH 44333, USA Direct: +1 330 836 1090 Fax: +1 330 839 1091

E-mail: info@bkt-tires.com www.bkt-tires.com

09/11- Balkrishna Tyres reserves the right to alter the details contained in the publication without prior notice.

“Step into the future, welcome to BKT’s world of Off-Highway Tyre Solutions”

